

ROUTE 145, WINTHROP ROAD
CHESTER, CONNECTICUT 06412-0684
TELEPHONE: (860) 526-9504
FAX: (860) 526-4078

California -compliant siren tone conversion will convert 49-state WS295HFS1-series, 5-series and 6-series sirens to produce tones in accordance with Title 13.

Installation Procedures . . .

1. Remove the cover from the control head by removing the four screws that hold the bezel to the cover, then sliding the chassis out.
2. Pry out the existing chip. Be sure to note the location of small alignment dot at one corner of the chip (see illustration). Gently pry the old chip up and out of the socket holder.


Note:

You should use an IC inserter/extractor to remove and install the chip. They can usually be found at your local electronic parts store.

3. Check alignment of the chip legs, straighten as required.

4. Position the chip above the socket holder, insuring the "alignment dot" is in the proper location. Line up the legs with the socket holes, then gently press the chip into the socket using the inserter/extractor.
5. Re-assemble the unit and apply the included revision label to the underside of the housing.

NOTE: *If your siren is not working properly after modification, contact Whelen Tech. Support at: 1-860-526-9504, then 6 and then 1.*



**Existing Chip Part Number:
77-5400237*-1**

**Replacement Chip Part Number:
77-5400534*-1**

Note: The asterisk (*) in the above Part Numbers represents the revision level of that particular chip.