

Model 295SLSA1 Series

ELECTRONIC SIREN AMPLIFIER

“Hands Free” lets you keep both hands on the wheel, both eyes on the road and access three siren tones and On/Off. Scan-Lock™ feature lets you choose from 17 siren tones to preset during siren installation.

A compact, self-contained unit that is backward compatible to the 295HFSA1 and slightly shallower in design for under-dash/console mounting.

Now you can access siren tones using the Scan-Lock feature or check on/off status of your siren via an icon on your video system. 295SLS Series sirens are full function plus radio repeat and public address.



295SLSA1

FEATURES

- Selectable 100 or 200 watt output.
- Hands-free operation plus 17 Scan-Lock siren tones to choose from.
- User selectable siren tones at time of installation via a momentary switch located on the back of the unit secures siren tones for agency standardization.
- Customize the placement of each siren tone on the rotary knob.
- “Siren in use” icon driver.
- Faceplate volume control knob.
- Five-year warranty on amplifier.
- Two manual functions allow for additional siren tone choices.
- PTT (push to talk) switch on microphone overrides all siren functions.
- Combination On/Off and horn ring transfer switch.
- Pre-wired unidirectional microphone.
- Optional plug-in microphone.
- Adjustable preset radio repeat volume.
- Input polarity protection.

- Output short circuit protection.
- External spade-type fuse.
- Bi-polarity horn/ring control activation.
- “Aux Enable” activates siren tones via input (slide switch, power controls or relay-to-ground connection).
- Quick disconnect plug for ease of service or replacement.
- SI TEST®, fully diagnostic silent test of amplifier and speaker(s).
- Adjustable intensity backlighting soft LED non-glare green.
- Adjustable bail bracket allows the mounting of the siren in a variety of positions.
- Complements all Whelen’s under dash products.
- Optional 24 volt DC model available, contact factory.
- Dimensions: Height 2-1/2” (63mm) H x 6” (152mm) W x 7” (178mm) D .
- Weight: 3 lbs. 12 oz. (1.7kg)

MODELS

- 295SLSA1**.....12 VDC w/Hard-wired microphone
- 295SLSC1**:12 VDC, w/Plug-in microphone

WHELEN®
ENGINEERING COMPANY, INC.

51 Winthrop Road
Chester, Connecticut 06412-0684
(860) 526-9504 • Fax: (860) 526-4078
www.whelen.com

Whelen Engineering reserves the right to upgrade and improve products without notice.
© 2013 Whelen Engineering Company, Inc. Printed in U.S.A.
Code No. 12099B - 01/13