

# E2010 CENTRAL STATION CONTROL



## Activation Control

**Control and monitor your Mass Notification Product from a central location. The E2010 allows the user to issue system activations and collect remote siren status via RF link or landline.**

Features Whelen's field proven COMM/STAT™ Command and Status Monitoring protocols. For fast, secure, and reliable communication.

The E2010 supports all of the features that are available in Whelen's High-Power Voice and Siren product line, from individual Command selection to user programmed command scenarios or Call Keys. With the selection of one Call Key, an operator may prompt the encoder to issue multiple commands.

With the included computer accessory software, you can connect the E2010 to a PC for Windows® based programming and data archiving. Data is available through an ACCESS® database.

### E2010 FEATURES

- 4 line by 40 character backlit, LCD display
- 16 "HOT" call keys
- 40 auxiliary call keys
- 2 time-of-day call key activations
- 4 remote input call keys
- Automatic system polling
- Internal alarm tone
- 2 contact closure outputs for alarms
- Base radio interface
- Channel grant input for trunking radio systems
- Security keylock
- Printer port
- Battery backup for time and date
- Rugged, membrane keyboard
- Microphone for public address 2010

### COMPUTER INTERFACE FEATURES

- CD-ROM and 9 Pin "D" cable included
- "Windows®" based call key programming
- Add call key descriptions
- Hard drive archive of all activity
- Selective printouts for status by location or date



# E2010 CENTRAL STATION CONTROL



## Specification Data

### GENERAL

The E2010 Central Station Control is configured to make maximum use of Call Keys or pre-programmed scenarios. In addition, commands are grouped into easy to follow categories for Warning Tones, Digital Voice Messages, Direction (if applicable) and Status. A numeric keypad section allows for individual remote addressing.

A 4 line by 40 character LCD display shows all Keyboard and Status activity. Command and Status information are also sent to a printer port and a serial communication port for a PC.

All pre-programmed functions are stored in non-volatile memory. Time and date are protected by internal, rechargeable batteries.

A keylock is available to disable the keyboard, but all status information is still active.

### COMPUTER REQUIREMENTS

PC with 486DX or Higher CPU  
WINDOWS® 95, 98, XP, 7, 8, or 10

CD-ROM Drive

Comm. Port

**Hard Disk Space Required:**  
8 MB

### PRINTER OPTION

Optional. 9 pin, dot matrix, 120 CPS, tractor feed, with parallel cable. Designed to be used with an Okidata #184 printer.

### COMMUNICATIONS

**Transmitter Connection:**  
(Typical 1 of 2 transmitters).

Squelch.

Push to talk  
(N.O., N.C. contacts).

Transmit audio.

Receive audio.

Channel grant active (for trunking).

**Signalling:**  
DTMF 2 of 8 format. 10 digit transmit. 14-18 digit receive.

**Tone Level:**  
Audio level adjustable.

**Transmitter Delay:**  
User selectable delay times.

### DIMENSIONS

**Height:** 3"

**Width:** 17"

**Depth:** 9"

**Weight:** 4.5 lbs.

### ELECTRICAL

120 VAC, UL® Listed, wall mount transformer.

### ORDERING INFORMATION

#### E2010

Central station control unit.

#### E2010R

Central station control unit (rack mount).

#### E2010P

Printer option for Okidata #184 printer and cable.

### MASS NOTIFICATION PRODUCTS

**Whelen Engineering Company, Inc.**

51 Winthrop Road

Chester, Connecticut 06412-0684

860-526-9504

800-637-4736

www.whelen.com

iowsales@whelen.com

Whelen Engineering Company, Inc. reserves the right to upgrade its products with design improvements without notification.

© 2018 Whelen Engineering Company, Inc.

Printed in the U.S.A.

10884H-022018



*"Our Mass Notification Products  
Speak for Themselves"™*