

## Economical All Hazard Siren System

*Whelen's HORNET Series All Hazard Sirens provide an economical alternative for replacing outdated electro-mechanical sirens.*

### SYSTEM FEATURES

- **HORNET** - Speaker assembly
- Two-Compartment (Type I) natural finish aluminum cabinet
- Speaker includes one high efficiency 400 watt speaker driver
- 50' (15.24m) Cable
- Battery powered. Minimum of 15 minutes of full power output with batteries of our recommendation
- AC temperature compensated 5 amp battery charger
- Local controls or remote controls
- One power amplifier
- Rotor
- Electronic siren controller
- Tone generator timer
- Local control push-buttons
- **SI TEST®**
- Low Battery alarm
- Battery tray
- Lightning arrestor
- Six standard public warning tones: Wail, Whoop, Attack, Hi-Lo, Alert, Airhorn

### SYSTEM OPTIONS

- **Solar Option** – 2 each, 80 watt panels, with brackets and solar regulator
- **Batteries** – 2 each, Whelen approved batteries. Check Whelen's web site, [www.whelen.com](http://www.whelen.com) for other recommended batteries
- **Pole Top Bracket**

### SIREN ACTIVATION CONTROLS

Our VHF High and UHF siren activation control packages include the following:

- Radio
- Radio interface
- Tone or digital squelch
- 3-5dB gain omni-directional antenna with bracket
- 35' (10.67m) of RG58 antenna cable
- Polyphaser
- SI TEST
- Low battery alarm (two-way only)

Other features are dependant upon one or two-way controls. Whelen equipment can be interfaced with many different types of two-way radio communications products and systems. The following is offered as standard options. Contact the factory for special applications.



HORNET mounted on Rotor



The following are available as standard options. **BOLD BLUE** indicates the Whelen Model:

### ONE-WAY CONTROLS

- **HAUXIN** - Auxiliary board for contact closure activation
- **HD2030LL** - 10 digit DTMF landline activation
- **HD230NV** - 10 digit DTMF VHF high band narrow band / 138-174 Mhz
- **HD230NU** - 10 digit DTMF UHF narrow band / 450-470 Mhz
- **HORTT** - Two-tone sequential option

### TWO WAY CONTROLS

- **HAUXCS** - Two-way contact closure activation and status board
- **HC2030LL** - Two-way landline activation
- **HC230NV** - 10 digit DTMF VHF high band narrow band / 138-174 Mhz
- **HC230NU** - 10 digit DTMF UHF narrow band / 450-470 Mhz

### OPTIONS

- **HSTATUS** - Cabinet window LED status indicator
- **HPGINT** - Paging interface to interface Whelen tones with existing paging systems
- **HINTRU** - Intrusion alarm (available with two-way only)

## Specifications

Component	Height Inches (CM)	Width Inches (CM)	Depth Inches (CM)	Weight Lbs. (kg)
<b>HORNET Speaker &amp; Rotor</b>	41.0 (104.2)	30.5 (77.5)	23.0 (58.4)	100 (45.4)
<b>Electronics Cabinet Type I</b>	32.5 (82.6)	22.5 (57.2)	10.5 (26.7)	67 (30.5)*
<b>Pole Top Bracket (Optional)</b>	See Drawing			71 (32.3)

\* Less batteries. Two batteries, add 90 Lbs. (40.9kg)

## Electrical

- **Battery Charger Input:** 120VAC, 60Hz, 7A Fuse
- **Battery Charger Output:** 28VDC, 5A (nominal)
- **Batteries:** 2-12V, 60AH Lead Calcium (user supplied)
- **Standby Current:** 82mA
- **Operating Current:** 22A, 24VDC
- **Power Amplifier Output Power:** 400 watts

## Environmental

- **Operating temperature:** -35C to +60C
- **Storage temperature:** -65C to +125C
- **Humidity, non condensing:** 0 to 95%

## Ordering Information

### BASIC SYSTEM INCLUDES ALL OF THE FOLLOWING

- **HORNET** - Speaker assembly & electronics cabinet

### OPTIONS

- **HAUXIN** (one-way) / **HAUXCS** (two-way) - Auxiliary boards for contact closure activation
- **HD2030LL / HD230NV / HD230NU** - One-way radio controls
- **HC2030LL, HC230NV / HC230NU** - Two-way radio controls
- **HORTT** - Two-tone sequential
- **HSTATUS** - Cabinet window LED status indicator
- **HPGINT** - Paging interface to interface Whelen tones with existing paging systems
- **HINTRU** - Intrusion alarm
- **HSBC80** - Solar power ①
- **HPTB** - Speaker pole top bracket
- **BSETHOR** - One pair of batteries

### NOTES

- ① Solar power option includes 2 - 80 watt panels, mounting bracket and regulator

## Hornet Acoustic Performance

**Wattage:** 400 watts  
**Estimated 70dB Range:** 2400 ft / 730 m

### MASS NOTIFICATION PRODUCTS

**Whelen Engineering Company, Inc.**  
 51 Winthrop Road  
 Chester, Connecticut 06412-0684  
 860-526-9504  
 800-637-4736  
 www.whelen.com  
 iowsales@whelen.com

Whelen Engineering Company, Inc.  
 reserves the right to upgrade its products with  
 design improvements without notification.  
 © 2018 Whelen Engineering Company, Inc.  
 Printed in the U.S.A.  
 103901-040918



**"Our Mass Notification Products  
 Speak for Themselves"™**

