

**All Hazard High-Power Siren System**

*Whelen's OMNI-ALERT™ Series Provides an economical alternative for powerful omni-directional siren warning without compromising quality.*

**SYSTEM FEATURES**

- **OA2** - Two omni-directional speaker cells assembled in a vertical column
- Two-compartment (Type I) natural finish aluminum cabinet
- Speaker cell includes two high efficiency 400 watt **EZ-PULL™** speaker drivers
- Pole top mounting bracket included
- Battery powered. Minimum of 15 minutes of full power output with batteries of our recommendation
- AC temperature compensated 5 amp battery charger
- 50' (15.24m) cable included
- Two power amplifiers
- Local controls or remote controls
- Electronic siren controller
- Tone generator timer
- Local control push-buttons
- **SI TEST®**
- Low battery alarm
- Battery tray
- Lightning arrestor
- Six standard public warning tones - Wail, Whoop, Attack, Hi-Lo, Alert, Airhorn

Optional Solar panel and VisuAlert™ 360° LED warning lights below OA2



Type I Electronic Cabinet



**SYSTEM OPTIONS**

- **Solar option** – 2 each 80 watt panels, with brackets and solar regulator.
- **Batteries** – 2 each Whelen approved batteries. Check Whelen's web site ([www.whelen.com](http://www.whelen.com)) for other recommended batteries.
- **VisuAlert™** – Omni-Directional visual warning Model **VALERT\*** for OA Series
- **L31H\*F4** – Top mount high dome beacon for OA Series, 24 VDC

**SIREN ACTIVATION CONTROLS**

Our VHF High and UHF siren activation control packages include the following:

- Radio
- Radio Interface
- Tone or digital squelch
- 3-5 dB Gain Omni-Directional Antenna with Bracket
- 35' (10.67m) of RG58 Antenna Cable
- Polyphaser
- SI TEST

Other features are dependant upon one or two-way controls. Whelen equipment can be interfaced with many different types of two-way radio communications products and systems. The following is offered as standard options. Contact factory for special applications.

**ONE-WAY CONTROLS**

- **OAUXIN** - Auxiliary board for contact closure activation
- **OD2030LL** - 10 Digit DTMF landline activation
- **OD230NV** - 10 Digit DTMF VHF High-Band Narrow-Band / 138-174 MHz
- **OD230NU** - 10 Digit DTMF UHF Narrow-Band / 450-470 MHz
- **OTT** - Two tone sequential option

**TWO-WAY CONTROLS**

- **OAUXCS** - Two-way contact closure activation and status board
- **OC2030LL** - Two-way landline activation
- **OC230NV** - 10 digit DTMF VHF High-Band Narrow-Band / 138-174 MHz
- **OC230NU** - 10 Digit DTMF UHF Narrow-Band / 450-470 MHz

**OPTIONS**

- **OSTATUS** - Cabinet window LED status indicator
- **OPGINT1** - Paging interface to interface Whelen tones with existing paging systems
- **OINTRU** - Intrusion alarm (available with two-way only)

# OA2 Two Cell



## Specifications

Component	Height Inches (CM)	Width Inches (CM)	Depth Inches (CM)	Weight Lbs. (kg)
OA2 Speaker	31.20 (79.24)	33.4 (84.84)	–	168 (76.20)
Electronics Cabinet Type I (Aluminum)	32.5 (82.6)	22.5 (57.2)	10.5 (26.7)	62 (28.2)
Pole Top Bracket	30.5 (77.47) (with top plate)	12.0 (30.5) x 13.5 (34.3)	See Drawing	71 (32.20)

Batteries add 90 lbs. Pallets, boxes and skids add weight.  
Check with Whelen if a freight quote is needed.

## Electrical

- **Battery Charger Input:** 120VAC, 60 Hz, 7A Fuse
- **Battery Charger Output:** 28VDC, 5A (nominal)
- **Batteries:** (2) 12V, 60AH lead calcium (user supplied)
- **Standby Current:** 82mA, 24VDC
- **Operating Current:** 44A, 24VDC
- **Power Amplifier Output Power:** 800 watts

## Environmental

- **Operating Temperature:** -35C to +60C
- **Storage Temperature:** -65C to +125C
- **Humidity, Non-Condensing:** 0 to 95%

## Ordering Information

### BASIC SYSTEM INCLUDES ALL OF THE FOLLOWING

- **OA2** - Speaker Assembly, Electronics Cabinet & Pole Top Bracket
- OPTIONS**
- **OAUXIN** – Auxiliary board for contact closure activation.
- **OAUXCS** – Auxiliary / status control board for contact closure activation and status
- **OD2030LL, OD230NV, OD230NU** – One-way narrow band radio control
- **OC2030LL, OC230NV, OC230NU** – Two-way narrow band radio control / status monitoring, COMM/STAT™
- **OTT** – Two-tone sequential
- **OSTATUS** – Cabinet window LED status indicator
- **OPGINT1** – Paging interface to interface Whelen tones with existing paging systems
- **OINTRU** – Intrusion alarm
- **OSBC280** – Solar power, 2 x 80W
- **OBATT** – One pair of batteries
- **VALERT\*** – VisuAlert™ 360° highly effective LED warning accessory
- **L31H\*F4** – L31 LED, 24VDC

\* Replace symbol in model number with letter indicating LED color desired:  
A = Amber; B = Blue; C = Clear/White; R = Red; RC = Red/White

### NOTES

- ① 10 digit DTMF Controls • Landline • VHF High-Band / 138-174 MHz • UHF / 450-470 MHz  
Our VHF High and UHF activation control packages include tone squelch, radio, radio interface, 3-5dB gain omni-directional antenna with bracket, 35' (10.67m) of RG58 antenna cable and polyphaser.

## OA2 Acoustic Performance

**Wattage:** 800 watts

**Estimated 70dB Range:** 2,200 ft / 670 m

Weather, terrain and other structures may impact the range. Each siren within the system may have a decreased or increased range depending on conditions beyond our control.

## MASS NOTIFICATION PRODUCTS

Whelen Engineering Company, Inc.

51 Winthrop Road  
Chester, Connecticut 06412-0684  
860-526-9504  
800-637-4736

www.whelen.com  
iowsales@whelen.com

Whelen Engineering Company, Inc.  
reserves the right to upgrade its products with  
design improvements without notification.  
© 2018 Whelen Engineering Company, Inc.  
Printed in the U.S.A.  
11695K-040918



*"Our Mass Notification Products  
Speak for Themselves"™*

