

# WPS2900 Series



## Six Standard Warning Tones

TONE	TONE SYMBOL	FREQUENCY	SWEEP RATE
WAIL		410 - 675	4 sec/1 sec
ALERT		560	Steady
HI/LO		465/650	.8 sec/.8 sec
ATTACK		410 - 490	1 sec/1 sec
AIR HORN		465 - 650	Modulated/1.6 sec
WHOOOP		300 - 465	3

**Performance chart footnotes** \*All 100' performance levels listed represent repeatable results with +/- 1dB to stated levels under free field conditions when warning systems are maintained to factory specification and tested according to published guidelines. Estimated 70dB and 60dB perimeters are based on the Federal Emergency Management Agency's -10dB per distance doubled path model, discussed in FEMA publication CPG 1-17, "Guide to Outdoor Warning Systems."



**"Our Mass Notification Products  
Speak for Themselves"™**

### MASS NOTIFICATION PRODUCTS

**Whelen Engineering Company, Inc.**

51 Winthrop Road  
 Chester, Connecticut 06412-0684  
 860-526-9504  
 800-637-4736  
 Fax: 860-526-4784  
 www.whelen.com  
 iowsales@whelen.com

Whelen Engineering Company, Inc.  
 reserves the right to upgrade its products with  
 design improvements without notification.  
 © 2015 Whelen Engineering Company, Inc.  
 Printed in the U.S.A.  
 12748B-071715