



### LIGHT ARRAYS



# WeCanX<sup>®</sup> 2250 **Light Arrays**

Our newest lightbar, the WeCanX 2250 Warning Light Array and Traffic Advisor packs more power into a sleeker design with a wide variety of light configurations to meet your needs. Combining the performance and reliability of our powerful ION<sup>®</sup> T-Series<sup>®</sup> lightheads with the customization and control of WeCanX, its versatility makes it an ideal lighting solution for a wide range of applications such as ambulances and fire apparatus.

WeCanX 2250 is slimmer than our 4500 Series, provides warning options, and allows aerial recognition. Choose flat end caps, or angled to create a unique, multi-angled light spread. Snap-in assembly allows lightheads to be easily removed for customization and field serviceability. Whelen Command<sup>®</sup> enables endless configurations, and lighthead placements are easily arranged within WeCad<sup>\*</sup>.

# WeCanX<sup>®</sup> 2250 Light Arrays

## **FEATURES**

- Utilizes powerful ION T-Series lightheads with patented E Block<sup>®</sup> technology to prevent moisture from entering the lighthead
- 3" slimmer than 4500 series
- Flush mount (slide bolt)
- Powered by WeCanX technology
- Functionality configurable in Whelen Command<sup>®</sup>
- Lighthead configurations easily defined within Whelen's WeCad<sup>™</sup> Software
- DUO<sup>®</sup> support in warning light options
- Angled or flat end caps
- Available in multiple lengths
- Aerial recognition option



## SPECS

Voltage: 10-30 VDC Certifications: SAE Class 1 Warranty: 5-Year Warranty Dimensions: 2.28" D x 1.66" (2.57" with Vertex") H x 30" L (6-light), 40" L (8-light), 50" L (10-light), 60" L (12-light), 70" L (14-light), 80" L (16-light)

IP67 rated lightheads



Angled End Cap





Flat End Cap



## WeCanX<sup>®</sup> 2250 Light Arrays

| WeCanX 2250 Super-LED <sup>®</sup> with Angled End Caps, Ordered Separately |  |  |
|---|--|--|
| WX2230  | 30" Long, 6 Lightheads and 2 Angled End Caps Required  |  |
| WX2240  | 40" Long, 8 Lightheads and 2 Angled End Caps Required  |  |
| WX2250  | 50" Long, 10 Lightheads and 2 Angled End Caps Required |  |
| WX2260  | 60" Long, 12 Lightheads and 2 Angled End Caps Required |  |
| WX2270  | 70" Long, 14 Lightheads and 2 Angled End Caps Required |  |
| WX2280  | 80" Long, 16 Lightheads and 2 Angled End Caps Required |  |

#### WeCanX 2250 Super-LED with Flat End Caps, Ordered Separately

| WX2220F | 22" Long, 4 Lightheads and 2 Flat End Caps Required  |  |
|---------|--|--|
| WX2230F | 32" Long, 6 Lightheads and 2 Flat End Caps Required  |  |
| WX2240F | 42" Long, 8 Lightheads and 2 Flat End Caps Required  |  |
| WX2250F | 52" Long, 10 Lightheads and 2 Flat End Caps Required |  |
| WX2260F | 62" Long, 12 Lightheads and 2 Flat End Caps Required |  |
| WX2270F | 72" Long, 14 Lightheads and 2 Flat End Caps Required |  |
| WX2280F | 82" Long, 16 Lightheads and 2 Flat End Caps Required |  |
|         |  |  |

#### Visit WeCad<sup>®</sup> to configure your WeCanX 2250 Light Array

WARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.

All products proudly designed, manufactured, and assembled in the U.S.A. ISO 9001 Registered QMS

Whelen Engineering reserves the right to upgrade and improve products without notice.

© 2023 Whelen Engineering Company, Inc. Printed in U.S.A. Code No. 13424D - 3/1/23



22FC

#### Options

| 22L#    | Add One DUO™ Color Lighthead, R/W, B/W, A/W, R/B, R/A, B/A   |
|---------|--|
| 22AEC   | One Angled End Cap, No Charge When Purchased with a 2250 Series                                    |
| ССР     | Core <sup>™</sup> Control Point for use with WeCanX Device when NOT using CenCom Core <sup>®</sup> |
| 22RECA  | One Angled Right End Cap for use with One Aerial Recognition Light, for Bars 30" to 50"            |
| 22LECA  | One Angled Left End Cap for use with One Aerial Recognition<br>Light, for Bars 30" to 50"          |
| 22RECA2 | One Angled Right End Cap for use with One Aerial Recognition Light, for Bars 60" to 80"            |
| 22LECA2 | One Angled Left End Cap for use with One Aerial Recognition<br>Light, for Bars 60" to 80"          |
| 22ARL*  | Add One Aerial Recognition Light, Amber, Blue, Green, White or Red                                 |
| 22LOAD  | Add One Load Light   |
| 22BLANK | Blank Filler Panel, Not Available for Angled End Caps  |
| 22EC    | One Flat End Cap for Left or Right Side  |
|         |  |

\* Replace symbol in model number with letter indicating desired color: R=Red, B=Blue, A=Amber, W=White, G=Green

# Replace symbol in model number with letter indicating desired color:

D=(Red/White), E=(Blue/White), F=(Amber/White), J=(Red/Blue), K=(Red/Amber), M=(Amber/Blue)



51 Winthrop Road Chester, Connecticut 06412-0684 (860) 526-9504 · www.whelen.com @WhelenENG f I in Y