≥

L41 Series

SUPER-LED® BEACON

Featuring Whelen's innovative Super-LED technology, the L41 is a high performance beacon with multiple flash patterns.



- SAE Class 1 Certified
- · Medium profile, smooth polycarbonate dome
- Cast aluminum powder coated base
- Full reverse polarity protection
- •100% solid-state electronics
- Hard-coated domes minimize environmental damage from sand, sun, salt, and road chemicals
- Fully encapsulated for moisture, vibration, and corrosion resistance
- 25 total selectable flash patterns (including steady-burn)
- •75 SignalAlert flashes per minute
- Available in permanent, magnetic, or magnetic/suction mount models
- Rated for thousands of hours of use
- · Virtually no RFI/EMI radiation
- · Dual voltage, 12/24VDC
- •12VDC 1.5 Amp (peak), 0.6 Amp (average)
- 24VDC .75 Amp (peak), 0.3 Amp (average)
- 4-3/4" (121mm) H x 6-7/16" (164mm) Dia.
- Five-year warranty

PERMANENT MOUNT MODELS

- Combination mounting: 1" pipe/permanent
- · Supplied with a 6" pigtail
- Synchronize with up to 8 Whelen beacons
- · Photocell Hi/Low mode available, contact factory
- Hi/Low intensity control

MAGNETIC & MAGNETIC/ SUCTION MOUNT MODELS

• Supplied with a 10' cord and cigar plug with built-in On/Off switch with LED "On" indicator and pattern control selection switch





MODELS

L41*P	Amber, Blue, Red, or White, Permanent/Pipe mount	
L41*M	Amber, Blue, Red, or White, Magnetic mount	
L41*V	Amber, Blue, Red, or White, Magnetic/Suction mount	



Replace * symbol in model number: A = Amber, B = Blue, R = Red, C = White

The use of magnetic or vacuum/suction mounted beacons mounted on the roof
or exterior of a vehicle in motion is at the sole discretion and risk of the user

OPTION

L40BG	Branch guard	

MARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit wheelings.com/regulatory.

