M2 SERIES

LIGHTHEADS

With a unique lens shape and patented Linear-LED° or TIR' reflector assembly, M Series" lightheads are completely illuminated for unmatched high-intensity warning and low current consumption. The M2's compact footprint makes it ideal for installation in areas where space is limited, like grilles and push bumpers.



ML2DJ

M2 LINEAR LIGHTHEAD FEATURES

- · Available with Clear, Color, or Smoked lenses
- Hard-coated lenses resist environmental damage from sand, sun, salt, and road chemicals
- · Mounts to surface via two screws for easy installation
- SOLO[™] and DUO[™] models have 74 Scan-Lock[™] flash patterns
- DVI[™] flash patterns
- Patented E Block[™] technology creates a watertight seal around the unit's stranded wires to prevent moisture from entering the lighthead
- STEADY-LOCK sets lightheads to Steady automatically when used with a CenCom Core® control system

SPECS

12 VDC Voltage:

Peak: 1.0 amp Current:

Average: 0.45 amp

Certifications: KKK-1822F, NFPA 1901, NFPA 1917,

SAE, and EC65 specifications

Warranty: 10-Year warranty

0.9" 3.7" (23mm) (93mm) (53mm) M2 SERIES MFG in USA SAE-W1-10

M2 LINEAR MODELS

	ML2*	SOLO, Warning Light, Amber, Blue, White, Green or Red, with Color Lens
	ML2*C	SOLO, Warning Light, Amber, Blue, White, Green or Red, with Clear Lens
	ML2*X	SOLO, Warning Light, Amber, Blue, White, Green or Red, with Smoked Lens
	ML2D#	DUO, Warning Light, Red/White, Blue/White, Amber/ White, Green/White, Red/Blue, Red/Amber, Red/Green Blue/Amber, or Amber/Green Only, with Clear Lens
	ML2D#X	DUO, Warning Light, Red/White, Blue/White, Amber/ White, Green/White, Red/Blue, Red/Amber, Red/Green Blue/Amber, or Amber/Green Only, with Smoked Lens


OPTIONS


M2FC	Flange Mount, Chrome	
M2FB	Flange Mount, Black	
M2GROM	Grommet Mount Kit, Black	
M2PEDB	Pedestal Mount Kit, Black	
M2PEDC	Pedestal Mount Kit, Chrome	



*REPLACE SYMBOL IN MODEL NUMBER WITH LED COLOR DESIRED: A=AMBER, B=BLUE, C=WHITE, G=GREEN, R=RED

REPLACE SYMBOL IN MODEL NUMBER WITH LED COLOR DESIRED: D=RED/WHITE, E=BLUE/WHITE, F=AMBER/WHITE, H=GREEN/WHITE, J=RED/BLUE, K=RED/AMBER, L=RED/GREEN, M=BLUE/AMBER, P=AMBER/GREEN





M2 SERIES

LIGHTHEADS

With a unique lens shape and patented Linear-LED® or TIR® reflector assembly, M Series® lightheads are completely illuminated for unmatched high-intensity warning and low current consumption. The M2's compact footprint makes it ideal for installation in areas where space is limited, like grilles and push bumpers.





M2 TIR LIGHTHEAD FEATURES

- · Available with Clear or Color lenses
- Hard-coated lenses resist environmental damage from sand, sun, salt, and road chemicals
- · Mounts to surface via two screws for easy installation
- SOLO" models have 25 Scan-Lock" flash patterns
- · Split models have 69 Scan-Lock flash patterns

SPECS

Voltage: 12 VDC


Current: Peak: 1.0 amp

Average: 0.45 amp

Certifications: KKK-1822F, NFPA 1901, NFPA 1917,

SAE, and EC65 specifications

Warranty: 10-Year warranty



M2 TIR MODELS

M2*	SOLO, Warning Light, Amber, Blue, White, or Red, with Color Lens
M2*C	SOLO, Warning Light, Amber, Blue, White, or Red with Clear Lens
M2#	SOLO, Warning Light, Split Color, Red/White, Amber/ White, Red/Blue, or Red/Amber Only, with Clear Lens
M2W*	SOLO, Warning Light, Wide Angle, Amber, Blue, White, or Red, with Color Lens
M2W*C	SOLO, Warning Light, Wide Angle, Amber, Blue, White, or Red, with Clear Lens
M2W#	SOLO, Warning Light, Wide Angle, Split Color, Red/ White, Red/Blue, Red/Amber Only, with Clear Lens

OPTIONS

M2FC	Flange Mount, Chrome
M2FB	Flange Mount, Black
M2GROM	Grommet Mount Kit, Black
M2PEDB	Pedestal Mount Kit, Black
M2PEDC	Pedestal Mount Kit, Chrome



REPLACE * SYMBOL IN MODEL NUMBER: A=AMBER, B=BLUE, C=WHITE, R=RED. REPLACE # SYMBOL IN MODEL NUMBER WITH SPLIT OR DUO COLOR DESIRED: D=RED/WHITE, F=AMBER/WHITE, J=RED/BLUE, K=RED/AMBER

MARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit when.com/regulatory.

