I

ION[™] Series[™]

LIGHTHEADS

Engineered for optimal durability and versatility, the ultra compact ION Series provides high intensity warning or illumination. Models are available in a variety of sizes, optics, and configurations for every application.











FEATURES

- · Single or split color models
- TIR directional or wide-angle light spread models
- · Available in universal or surface mount
- Universal mount models include combination permanent/pedestal, clip, edge mounts, and doublesided tape, with a Black or White housing
- Universal mount options include bail/swivel bracket in Black or White, rubber grommet, and pedestal mount in Black or White
- Surface mount models include flange, available in Black, White, or Chrome
- Single color models have 25 Scan-Lock flash patterns
- Split color models have 69 Scan-Lock flash patterns
- Supplied with 10" 4-wire pigtail

SPECS

Voltage: 12 VDC

AMP: 0.40 amps (average)

Certifications: SAE Class 1 Certified (smoked or

colored domes), Wide-angel sur face mount lighthead meets NFPA 1901, KKK 1822F requirements

Dimensions: Universal mount size: 4" (101mm) L

x 1" (25mm) H x 1.25" (32mm) D Surface mount size: 5.94" (150mm) L x 1.69" (43mm) H x 1.13" (28mm) D

Warranty: 10-year warranty

ION SERIES

Universal N	Mount
ION*	Red, Blue, Amber, or White
ION#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens
XON*	Red, Blue, Amber, or White, Smoked lens
XON#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Smoked lens
Surface Mo	punt
IONSM*	Red. Blue. Amber. or White

Surface Mount	
IONSM*	Red, Blue, Amber, or White
IONSM#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens
XONSM*	Red, Blue, Amber, or White, Smoked lens
XONSM#	Split Amber/Blue, Amber/White, Blue/Red, or White/Red only, Smoked lens

Wide-Angle Universal Mount	
WION*	Red, Blue, Amber, or White
WION#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens
WXON*	Red, Blue, Amber, or White, Smoked lens
WXON#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Smoked lens

Wide-Angle S	de-Angle Surface Mount	
WIONSM*	Red, Blue, Amber, or White	
WIONSM#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red only, Clear lens	
WXONSM*	Red, Blue, Amber, or White, Smoked lens	
WXONSM#	Split, Amber/Blue, Blue/Red, or White/Red only, Smoked lens	



Replace symbol * in model number with letter indicating color desired:

A = Amber, B = Blue, C = White, R = Red

Replace # symbol in model number with letter indicating split color desired: D=Red/White, F=Amber/White, J=Red/Blue, K=Red/Amber, M=Blue/Amber. For White or Chrome housings, contact factory.

MARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit wheelen.com/regulatory.





ION T-Series

LIGHTHEADS

The ION T-Series features advanced Linear Super-LED* optics in a sleek and low profile design, with a diameter of only .5".





FEATURES

- Available with SOLO or DUO (two color interleaved) technology and Linear Super-LED optics
- · Available in Amber, Blue, Red, and/or White
- SOLO models are available in single or split colors
- SOLO single color models have 25 Scan-Lock flash patterns, split color models have 69
- DUO models have 33 Scan-Lock flash patterns
- Easily surface mounts with two screws
- Includes Black flange and a 4-wire 6" (152mm) pigtail

SPECS

Voltage: 12 VDC

////////

AMP: SOLO: 0.33 amps (average,

DUO: 0.28 amps (average)

Dimensions: 5.14" (13.06cm) L x 1.50" (3.81cm) H x

.50" (1.27cm) D

MODELS

	Clear Lens	
	TLI*	Amber, Blue, Red, or White
	TLI#	Split Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only
	TLI2#	DUO Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only

Smoked Ler	ns
TLI*X	Amber, Blue, Red, or White
TLI#X	Split Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only
TLI2#X	DUO Amber/Blue, Amber/White, Blue/White, Red/Blue or Red/White Only



Replace * symbol in model number with color desired: **A**=Amber, **B**=Blue, **C**= White, **R**=Red Replace # symbol in model number with split or DUO color desired: **D**=Red/White, **E**=Blue/White, **F**=Amber/White, **J**=Red/Blue, **M**=Blue/Amber

MARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.



ION DUO TRIO

LIGHTHEADS

ION DUO and TRIO lightheads feature two color or three color interleaved LEDs and advanced Linear Super-LED optics

FEATURES

- Available in Red, Blue, Amber, and White combinations
- · Available in universal or surface mount
- Universal mount includes combination permanent/pedestal, clip, edge mounts, double-sided tape, with a Black or White housing
- Surface mount models include flange, available in Black, White, or Chrome

ION TRIO SERIES

- · Supplied with a 10" 6-wire pigtail
- Choose from any combination of color one, color two, and/or color three
- · Color three features steady-burn override
- 25 Scan-Lock flash patterns
- · Amp draw (each color) 0.40 amps (avg)

ION DUO SERIES

- Supplied with a 10" 5-wire pigtail
- Independent control of color one and color two
- 64 Scan-Lock flash patterns
- · Amp draw (each color) 0.28 amps (avg)

SPECS

Dimensions:

Universal mount size: 4" (101mm) L x 1" (25mm) H x 1.25" (32mm) D Surface mount size: 5.94" (150mm) L x 1.69" (43mm) H x 2" (50MM) D



MODELS

DUO Univers	sal Mount
I2J	Blue/Red
I2F	Amber/White
I2E	Blue/White
I2D	Red/White
I2M	Blue/Amber
XI2J	Blue/Red, Smoked lens
XI2F	Amber/White, Smoked lens
XI2E	Blue/White, Smoked lens
XI2D	Red/White, Smoked lens
XI2M	Blue/Amber, Smoked lens

DUO Surface	e Mount
I2SMJ	Blue/Red
I2SMF	Amber/White
I2SME	Blue/White
I2SMD	Red/White
I2SMM	Blue/Amber
XI2SMJ	Blue/Red, Smoked lens
XI2SMF	Amber/White, Smoked lens
XI2SME	Blue/White, Smoked lens
XI2SMD	Red/White, Smoked lens
XI2SMM	Blue/Amber, Smoked lens

TRIO Universal Mount	
I3JC	Red/Blue/White
I3JA	Red/Blue/Amber
13KC	Red/Amber/White
I3MC	Blue/Amber/White
XI3JC	Red/Blue/White, Smoked lens
XI3JA	Red/Blue/Amber, Smoked lens
XI3KC	Red/Amber/White, Smoked lens
XI3MC	Blue/Amber/White, Smoked lens

I3SMJC Red/Blue/White	
I3SMJA Red/Blue/Amber	
I3SMKC Red/Amber/White	
I3SMMC Blue/Amber/White	
XI3SMJC Red/Blue/White, Smoked lens	
XI3SMJA Red/Blue/Amber, Smoked lens	
XI3SMKC Red/Amber/White, Smoked lens	
XI3SMMC Blue/Amber/White, Smoked lens	



Replace symbol * in model number with letter indicating color desired:

A = Amber, B = Blue, C = White, R = Red Replace # symbol in model number with letter indicating split color desired: D=Red/White, E=Blue/White, F=Amber/White, J=Red/Blue, M=Blue/Amber For White or Chrome housings, contact factory.

MARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.





ION V-Series

LIGHTHEADS

Utilizing multiple planes of light in one lighthead, the ION V-Series is available in three-in-one combination or single color warning models.

FEATURES

- Combination models have 180° wide-angle warning, illumination, and puddle light
- Single color models have combination 180° and TIR directional warning
- · Available in universal or surface mount
- Universal mount models include combination permanent/pedestal mount, clip, edge mounts, and double-sided tape. Options include bail/ swivel bracket in Black or White, pedestal mount in Black or Chrome, and rubber grommet
- · Surface mount models include flange, available in Black, White, or Chrome
- Warning segment has 25 Scan-Lock[™] flash patterns
- · Warning segment available in Red, Amber, Blue, or White
- 6" pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead

SPECS

VDC:

Amp draw: Combination model - Warning

lights 0.76 amps (avg),

Alley lights 0.31 amps (average), Puddle lights 0.12 amps (average)

Single color warning model -

1.147 amps (average)

Dimensions: Universal mount size: 4.06"

(101mm) L x 1" (25mm) H x 2.19

(56mm) D

Surface mount size: 5.94" (150mm) L x 1.69" (43mm) H x 2"

(50MM) D







MODELS

	V-Series Universal Mount		Housing
	IONV3*	Combination, Red, Blue, Amber, or White	Black
	IONV1*	Single Color, Red, Blue, Amber, or White	Black
	XONV3*	Combination, Red, Blue, Amber, or White, Smoked lens	Black
	XONV1*	Single Color, Red, Blue, Amber, or White, Smoked lens	Black

V-Series Surface Mount		Housing
IONSV3*	Combination, Red, Blue, Amber, or White	Black
IONSV3*C		Chrome
IONSV1*	Single Color, Red, Blue, Amber, or White	Black
IONSV1*C		Chrome
XONSV3*	Combination, Red, Blue, Amber, or White, Smoked lens	Black
XONSV1*	Single Color, Red, Blue, Amber, or White, Smoked lens	Black



Replace symbol * in model number with letter indicating color desired: = Amber, B = Blue, C = White, R = Red, for White housings, contact factory.

OPTIONS

ION Series

IONK1B	Swivel mount bracket, Black
IONGROM	Grommet mount kit, Black
IONPEDB	Pedestal mount kit, Black
IONBKT1	Universal license plate bracket, horizontal mount, Black. For 2 ION Series lightheads, not for use with ION V-Series
IONBKT4	2013-2019 Ford Police Interceptor Utility, rear hatch mounting brackets (pair), Black. Requires 2 ION Series lightheads, purchased separately
IONBKT5	Universal mount, reversed. Remove screws without removing the light
IONBKT6	2015-2019 Chevy Tahoe, rear hatch mounting brackets (pair), Black. Requires 2 ION Series lightheads, purchased separately
IONBKT7	2015-2019 Chevy Tahoe, grille mount bracket. Requires 2 ION Series lightheads, purchased separately

ION T-Series™

	TIONFC	T-Series Chrome Flange
	TIONBKT1	T-Series "L" mounting bracket for 1 lighthead
	TIONBKT2	T-Series Universal license plate bracket for 2 lightheads
	TIONBKT3	T-Series "L" mounting bracket for 2 lightheads
	TIONBKT4	T-Series Universal over/under "L" mounting bracket for 2 lightheads







MARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.

All products proudly designed, manufactured, and assembled in the U.S.A.

• ISO 9001 Registered QMS

Whelen Engineering reserves the right to upgrade and improve products without notice. © 2023 Whelen Engineering Company, Inc. Printed in U.S.A. Code No. P12431K - 10/2023

